

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (currently amended): A flash memory access apparatus, comprising:

a flash memory comprising a plurality of units, each of the units comprising a plurality of blocks; and

a flash memory controller,

wherein if a write operation is requested for a logical block number of the flash memory, the flash memory controller is configured to write data and meta-information comprising flash memory state information comprising an indicator, which indicates a state of the physical block as valid, deleted, or invalid, in the physical block corresponding to a logical block with the logical block number if a previous write operation has not been performed for the logical block, and the flash memory controller is configured to perform a write operation for writing the data and the meta-information, comprising writing the valid indicator, allocated to the logical block in a new physical block without changing flash memory state information, wherein the flash memory state information is written in a previous physical block corresponding to the logical block if the previous write operation has been performed for the logical block,~~and~~

wherein the flash memory state information is time independent,

wherein the flash memory controller is configured to perform a recovery operation which detects, during a scanning process, physical blocks for the logical block number and recovers from an error by determining a valid block for the logical block among the detected physical blocks.

wherein the scanning process comprises reading a logical block number for each of the physical blocks by investigating the flash memory based on a latest accessed block, and investigating a field of a block allocation table corresponding to the read logical block number, and

wherein the investigating the field of the block allocation table comprises writing a state value of "1" in the field of the block allocation table if the state value has been "0," and detecting that the logical block number has been searched for through the previous physical block during the scanning process, if the state value is "1."

2. (previously presented): The apparatus as claimed in claim 1, wherein each physical block comprises:

- a first area, into which the data is written, and
- a second area, into which meta-information is written.

3. (original): The apparatus as claimed in claim 1, wherein the data and meta-information of the logical block are simultaneously written.

4. (previously presented): The apparatus as claimed in claim 1, wherein the meta-information further comprises the logical block number.

5. – 7. (canceled).

8. (currently amended): The apparatus as claimed in claim 51, wherein the recovery operation recovers from an error by determining a latest accessed physical block for the logical block number among the detected physical blocks according to priorities set during the scanning process, as the valid block, and rewriting flash memory state information written in other physical blocks of the detected physical blocks as deleted.

9. (currently amended): The apparatus as claimed in claim 51, wherein the recovery operation is performed during the initializing the flash memory.

10. (currently amended): The apparatus as claimed in claim 51, wherein the recovering from the error is performed during reclaiming the flash memory wherein the reclaiming comprises moving data written in a predetermined unit of the flash memory to a new unit.

11. (currently amended): A flash memory access method comprising:  
accessing the flash memory and searching for a currently writable physical block if a processor requests a write operation for a specific logical block number of the flash memory; and  
writing data and meta-information, comprising flash memory state information comprising an indicator which indicates a state of the physical block as valid, deleted, or invalid, in the physical block corresponding to a logical block with the logical block number if a previous write operation has not been performed for the logical block, and writing the data and the meta-information comprising writing the valid indicator in a new physical block corresponding to the logical block without changing flash memory state information, wherein the flash memory state

information is written in a previous physical block corresponding to the logical block if the previous write operation has been performed for the logical block,

wherein the flash memory state information is time independent,

the method further comprises a recovery operation comprising detecting, during a scanning process, physical blocks for the logical block number and of recovering from an error by determining a valid block for the logical block among the detected physical blocks, and

wherein the scanning process comprises:

reading a logical block number for each of the physical blocks by investigating the flash memory based on a latest accessed block, and investigating a field of a block allocation table corresponding to the read logical block number; and

writing a state value of "1" in the field of the block allocation table if the state value has been "0," and detecting that the logical block number has been searched for through the previous physical block during the scanning process, if the state value is "1."-

12. (previously presented): The method as claimed in claim 11, wherein each physical block comprises first and second areas, the method further comprising:

writing the data into the first area; and

writing the meta-information into the second area.

13. (original): The method as claimed in claim 11, wherein the data and meta-information of the logical block are simultaneously written.

14. (previously presented): The method as claimed in claim 11, wherein the meta-information comprises the logical block number, and the flash memory state information indicating a state of the physical block as valid, deleted, or invalid.

15. - 16. (canceled).

17. (currently amended): The method as claimed in claim ~~15~~11, wherein the recovering comprises recovering from the error by determining a latest data written among data of a specific logical block number detected during reclaiming the flash memory, and wherein the reclaiming comprises moving data written in a predetermined unit of the flash memory to a new unit.

18. – 21. (canceled).

22. (currently amended): A flash memory access apparatus, comprising:  
a flash memory comprising a plurality of units, each of the units comprising a plurality of  
blocks; and  
a flash memory controller,  
wherein if a write operation is requested for a logical block number of the flash memory,  
the flash memory controller is configured to write data and meta-information comprising flash  
memory state information comprising an indicator, which indicates a state of the physical block  
as valid, deleted, or invalid, in the physical block corresponding to a logical block with the  
logical block number if a previous write operation has not been performed for the logical block,  
and the flash memory controller is configured to perform a write operation for writing the data

and the meta-information, comprising writing the valid indicator, allocated to the logical block in a new physical block without changing flash memory state information, wherein the flash memory state information is written in a previous physical block corresponding to the logical block if the previous write operation has been performed for the logical block,

wherein the flash memory state information is time independent, and

~~The apparatus as claimed in claim 1,~~ wherein the flash memory controller is configured to perform a recovery operation to recover from an error and identify a valid block for the logic block, the recovery operation comprising:

detecting a last accessed physical block which is a lowermost physical block in a physical block unit that has been accessed the latest;

determining a last accessed logic block which corresponds to the detected last accessed physical block; and

changing a scanning identifier for the determined last accessed logic block to a first identifier in a block allocation table, if the scanning identifier of the determined last accessed logic block is different from the first identifier.

23. (previously presented): The apparatus as claimed in claim 22, wherein the recovery operation further comprises:

scanning remaining physical blocks in the physical block unit in an ascending order from the detected last accessed physical block; and

for each physical block, changing the scanning identifier of a corresponding logic block to a second identifier, if the scanning identifier of the corresponding logic block comprises the first identifier.

24. (previously presented): The apparatus as claimed in claim 23, wherein the recovery operation further comprises:

identifying the physical blocks which correspond to the same logic block; and  
changing the indicator of the memory state information of the identified physical blocks to deleted, if the scanning identifier of the logic block comprises the second identifier.

25. (previously presented): The apparatus as claimed in claim 23, wherein changing to the first identifier comprises writing a value of "1" in a field of the block allocation table if a previous value has been "0," and detecting that the logical block has been searched for through the previous physical block during the scanning process, if the value comprises "1."